

ISL 60 Plus Glazing Tape

Part of the Dixon
International Group Ltd
www.dig.co.uk

Introduction

ISL 60 Plus Glazing Tape is an intumescent, non-ceramic fibre glazing tape which is available on a roll. It has been specifically developed to achieve successful fire performance to BS and EN Standards for both doors and screens, and particularly for both timber and steel systems with toughened glass. For applications for 60, 90 and 120 minutes. Test evidence available on request.

The Product

ISL 60 Plus Glazing Tape has been developed to provide excellent high temperature insulation combined with the benefit of intumescence for sealing properties. It has excellent thermal stability properties up to 1260°C and with the benefits of a volume expansion of 2-3 times beginning at 325°C, it produces a medium pressure intumescence.

It is only available in a pale grey speckled colour.

Application


ISL 60 Plus Glazing Tape has an adhesive backing to allow rapid and easy installation into both fire door apertures and fire glazing screens. The material has excellent flexibility and can be cut very easily with scissors or a sharp knife so is very easy to fit to glazing beads and other precision-dependent applications. The highly insulating and intumescent behaviour allows it to be used across a very broad range of fire resistant glazings including integrity, semi-insulating and insulation glasses and it is particularly beneficial for systems comprising modified toughened or toughened borosilicate glasses.

It is suitable for use in both timber and steel fire rated glazing systems.




Available in 7.5m rolls ex stock

Fire Door Applications Steel and Timber Frames



Fire Screen Applications



Key

- | | | | |
|---|----------------------|---|---|
|  | Fire Resistant Glass |  | Softwood or Hardwood
Timber Beading |
|  | ISL 60 Plus Tape |  | Glazing Setting Block |
|  | Aperture Liner |  | Pins or Screws |
| | |  | Fire Door / Screen
- 30, 60, 90+ minutes
applications |

Description

ISL 60 Plus Glazing Tape is highly compressible and has good handling strength. The tape is made from biosoluble alkaline earth silicate fibres and it also contains vermiculite particles to produce the intumescence behaviour. This combination produces high insulation properties, intumescence and an excellent resistance to thermal erosion. It is lightweight with a density of 450kgm⁻³ and has excellent chemical stability however it is only suitable for indoor applications.

Continued overleaf

ISL 60 Plus Glazing Tape

Part of the Dixon
International Group Ltd
www.dig.co.uk

Sizes

ISL 60 Plus Glazing Tape is supplied in 7.5 metre length rolls and in standard widths of 15mm, 20mm and 25mm all at 5.8mm thickness - which can be easily compressed down to 4mm, if required for glazing applications. A 3mm thickness version is also available on request.

Contact our Technical Department for enquiries.



Contacting Us

Intumescent Seals, Brewery Road,
Pampisford, Cambridge,
CB22 3HG, England

Phone: 01223 832851

Fax: 01223 837215

Email: info@intumescentseals.co.uk



Design, Innovation & Manufacture since 1962

www.intumescentseals.co.uk



Made in
the UK

